



GTEN 2019 Symposium

October 21-23, 2019 | Banff, Alberta

HYDROGEN IN NATURAL GAS COMBUSTION AND COMPRESSION

Rainer Kurz, Luke Cowell, Terry Tarver, Avneet Singh
Solar Turbines Incorporated



Presented at the Gas Turbines Energy Network (GTEN) 2019 Symposium
Banff, Alberta, Canada - October 2019

The GTEN Committee shall not be responsible for statements or opinions advanced in technical papers or in symposium or meeting discussions.



Why?

- Renewables to be 2/3rds of capacity additions to 2040
- As installed capacity increases, greater flexibility is needed






The main methods for generating hydrogen

- Steam Methane Reformation (SMR): Using steam to split methane into H_2 and CO_2 . The CO_2 is generally sequestered as part of this process. This is referred to as blue hydrogen.
- Gasification of solid fuels like coal, pet coke, biomass, municipal waste into a syngas. This has which contains CO , CO_2 and other things is then processed to recover H_2 . This is referred to as brown hydrogen
- Electrolysis: Using electricity (often using excess renewables) to split H_2O into hydrogen and oxygen. This is referred to as green hydrogen
- Photolytic: Using light energy to split water into hydrogen and oxygen. This is also considered to be green hydrogen.



It's not cheap.....





Open Questions

- What is the impact of hydrogen in natural gas on gas turbine **combustion** and safety?
- What is the impact of Hydrogen on **transportation efficiency** in a pipeline?




Open Questions

- What is the impact of hydrogen in natural gas on gas turbine **combustion** and safety?
- What is the impact of Hydrogen on transportation efficiency in a pipeline?



Gas Turbine Combustion Systems






GTEN 2019 Symposium

Hydrogen Blend Combustion Characteristics

	H2% with Balance Pipeline NG					
H2 Blend	0%	5%	10%	20%	30%	100%
Combustion Parameters						
Laminar Flame Speed (cm/s)	124	127	130	139	150	749
Autoignition Delay Time (msec)	124	112	107	104	103	76
Wobbe Index (btu/scf)	1215	1199	1183	1150	1116	1039
Flame Temperature (°F) ¹	4206	4210	4215	4225	4238	4510
Package & Fuel System						
Flammability (% vol LEL)		4.83	4.79	4.71	4.63	4
Maximum Experimental Spark Gap (MESG)	1.10	1.06	1.02	.94	.86	.28
NEC/CSA & IEC Gas Groups	D & IIA	D & IIA	D & IIA	D & IIA	D & IIB	B & IIC



Emissions (Diffusion Flame)





Package Issues

- Safety
- Purge
- Failed Starts





H₂ Flammability range: 4%-75% by volume (Natural Gas: 5-15%)

H₂ Autoignition Temperature 500°C (Nat Gas : 580°C)

H₂ Ignition Energy: 0.02mJ (Nat Gas: 0.29mJ)


Flame Speed



Varying Levels of Propane, Butane and CO2 Mixed with Natural Gas Compared to Mixtures of Hydrogen and Natural Gas




Lean Premix-NO_x Emissions



NO_x Emissions Variation at Full Load and Standard Pilot with Associated Gas Test Fuels with Different Values of Adiabatic Flame Temperature



Lean Premix-NO_x Emissions



NO_x Emissions Variation at Combustion Rig Testing at Simulated Full Load Conditions for a 59°F Day and Constant Pilot Level with Varying Blends of Hydrogen Mixed with Natural Gas.



Combustion Summary

- Conventional combustion systems are proven for H_2 + NG blends up to 30%.
- Even for Lean Premix systems, H_2 + NG mixtures of 5 to 10% are not problem today.
- Concerns are related to safety, for example at failed starts. These are manageable with today's technology




Open Questions

- What is the impact of hydrogen in natural gas on gas turbine combustion and safety?
- What is the impact of Hydrogen on **transportation efficiency** in a pipeline?




Hydrogen Properties


- It's lighter
- Lower volumetric heating value
- Higher Heat capacity
- Different Viscosity



— Volume Calorific value, GCV, kWh/m³(n) - - - Normal mass density, ρ₀, kg/m³(n)



— @ Normal Condition, 0°C and 1 atm — @ 15°C & 40 bara
- - - @ 15°C & 80 bara - - - @ 55°C & 80 bara




— @ Normal Condition, 0°C and 1 atm - - - @ 15°C & 40 bara
- - - @ 15°C & 80 bara @ 55°C & 80 bara






Impact on Compression

- Operating points for constant inlet conditions and discharge pressure.
- Flow adjusted to maintain energy flow





Pipeline Simulation



Power Increase for Constant Energy Flow



Transport Efficiency

- Gas compressors are able to handle hydrogen in natural gas, but they will have to run faster (ie, re-stages may be required on existing units), and will consume more power.
- The transportation efficiency of pipelines will be reduced when hydrogen is added.



Summary

- It can be done
- Viable to Balance Renewables
- Economic Justification?
- What are realistic concentrations (based on production capability)